

Equipment

Dry Containers

The following sizes and designs dry containers are available:

- 20" with a payload up to 28.3 metric tons
- 40" – both 8'6" and 9'6" high cube – with a payload up to 30.4 metric tons
- 45" – 9'6" high cube – with a total capacity of 86 cubic meters

Dimension/Weight in m/kg

Dry / Steel		Door Openings (mm)		Internal Dimensions (mm)			Weight (kg)			Volume (m ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	Capacity to load line
20" std	20' x 8' x 8' 6"	2,340	2,274	5,896	2,350	2,385	27,000	2,150	24,850	33
40" std	40' x 8' x 8' 6"	2,339	2,274	12,035	2,350	2,393	32,500	3,700	28,800	67
40" high	40' x 8' x 9' 6"	2,340	2,577	12,035	2,350	2,697	34,000	3,800	30,200	76
45" high	45' x 8' x 9' 6"	2,340	2,585	13,556	2,352	2,697	32,500	4,800	27,820	86

Dry / Aluminium		Door Openings (mm)		Internal Dimensions (mm)			Weight (kg)			Volume (m ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	Capacity to load line
40" wide door	40' x 8' x 8' 6"	2,343	2,278	12,056	2,347	2,379	32,500	2,790	29,710	67
40" high	40' x 8' x 9' 6"	2,343	2,584	12,056	2,347	2,684	32,500	2,900	29,600	76
45" high	45' x 8' x 9' 6"	2,340	2,584	13,582	2,347	2,696	32,500	3,900	28,600	86

Dimension/Weight in ft/lb

Dry / Steel		Door Openings (ft)		Internal Dimensions (ft)			Weight (lb)			Volume (ft ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	Capacity to load line
20" std	20' x 8' x 8' 6"	7'8 1/16"	7'5 1/2"	19'4 1/16"	7'8 1/2"	7'9 7/8"	59,523	4,739	54,783	1,179
40" std	40' x 8' x 8' 6"	7'8 1/16"	7'5 1/2"	39'5 13/16"	7'8 1/2"	7'8 1/2"	71,648	8,156	63,491	2,390
40" high	40' x 8' x 9' 6"	7'8 1/16"	8'5 7/16"	39'5 13/16"	7'8 1/2"	8'10 3/16"	74,954	8,377	66,577	2,714
45" high	45' x 8' x 9' 6"	7'8 1/16"	8'5 3/4"	44'5 11/16"	7'8 9/16"	8'10 3/16"	71,648	10,317	61,330	3,071

Dry / Aluminium		Door Openings (ft)		Internal Dimensions (ft)			Weight (lb)			Volume (ft ³)
Type	Size	Width	Height	Length	Width	Height to load line	Max. Gross	Tare	Max. Payload	Capacity to load line
40" wide door	40' x 8' x 8' 6"	7'8 3/16"	7'5 11/16"	39'6 9/16"	7'8 3/8"	7'9 5/8"	71,648	6,150	65,497	2,393
40" high	40' x 8' x 9' 6"	7'8 3/8"	8'5 11/16"	39'6 9/16"	7'8 3/8"	8'9 5/8"	71,648	6,393	65,254	2,714
45" high	45' x 8' x 9' 6"	7'8 1/16"	8'5 11/16"	44'6 11/16"	7'8 3/8"	8'10 1/8"	71,648	8,597	63,050	3,071